

FIRE RATED DOWNLIGHTS

About nelux

After 15 years working in european lighting market, we decide to settle down our head office in Hong Kong in 2010. Since 1995 in the custom made light fixtures in Europe and since 2010 working as lighting product designers.

We have two lines of work:

Management mould manufacturing
Nelux design and produce the product you
need .Design and consultancy department
specialized in custom manufacturing tooling
machining lighting products for your lighting
projects , designing your own light fixtures
for your own projects. From Nelux we put our
knowledge at your service for the execution
of all processes from the design and creation
of a lighting product to its production

Our products

Nelux Architectural lighting product designers company, offer a huge range of products specifically for architectural lighting applications and high-end lighting projects. The main benefits of our products are low power consumption and high reliability. Our LED lighting products utilize only the best and most current components.




- 1. 30 60 90 min Fire Rated approval by SGS BS 476-21
- 2. IP65
- 3. 100% Patent design.

3000K 4000K 5000K

- 4. Three color change and Dim-to-warm available.
- 5. Interchangeable bezel by twist & lock style, White, black,Chrome, polished chrome ,brushed nickle surface treatment for option
- 6. CE ROHS.
- 7. Size:Dia85*H56.5mm,Cut Out:72-75mm
- 8. TUYA Bluetooth and WIFI, Wireless smart control





Twist And lock

Bezels:













Strong cooling



Die casting body, surface wrinkle treatment, effectively increasing the cooling area, good heat dissipation, let light remained in critical temperature to achieve a longer life.

Anti-Glare



LED lighting products up to 46° shading angle, can effectively prevent the glare of downlights. Human visual areas to withstand the maximum average level for more than 30°, can control the light glare outside so as to effectively reduce the glare of downlights.



Model: NL8FHB21

Power:8W

Input voltage:AC 220-240V Beam angle:38°/60° Luminous Flux:580-650lm

CRI:Ra>80

CCT:3000K/4000K/5000K Material:Aluminum

Color:White/Gray

Optional:Triac PWM dim, 0-10Vdim,

DALI dim driver







3000K





Simulation effect



Adopt space: All types of public places, restaurants, shops, car showrooms, brand stores, department stores, supermarkets, museums, office halls, homes, etc.



Model: NL10FHB21

Power:10W

Input voltage:AC 220-240V Beam angle:38°/60°

Luminous Flux:750-850lm

CRI:Ra>80


CCT:3000K/4000K/5000K


Material:Aluminum

Color:White/Gray

Optional:Triac PWM dim, 0-10Vdim, DALI dim driver







Simulation effect





/////-

Model: NL6FHC24

Power:6W

Input voltage:AC 220-2405V Beam angle:38°/60°

Luminous Flux:500-550lm CRI:Ra>80


CCT:3000K/4000K/5000K

Material:Aluminum Color:White/Gray

Optional:Triac PWM dim, 0-10V dim, DALI dim driver

3000K







Model: NL68FHC24

Power:8W

Input voltage:AC 220-240V

Ø75mm

Beam angle:38°/60° Luminous Flux:650-700lm

CRI:Ra>80


CCT:3000K/4000K/5000K

Material:Aluminum

Color:White/Gray

Optional:Triac PWM dim, 0-10V dim,

DALI dim driver



Simulation effect



Simulation effect



The material, pure aluminum Of high quality, lightness and grace, effectively heat dissipation, ensuring LED chip longer life span.



Model: NL10FHG21

Power:9W

Input voltage:AC 220-240V

Beam angle:45°

Luminous Flux:800lm

CRI:Ra>80

CCT:3000K/4000K/5000K

Material:Aluminum

Color:White/Gray

Optional:Triac PWM dim, 0-10V dim, DALI dim driver

3000K






4000K





5000K





Simulation effect





Ø65mm

Model: NL6FHJ21

Power:6W

Input voltage:AC 220-240V

Beam angle:38°

Luminous Flux:600lm

CRI:Ra>80

CCT:3000K/4000K/5000K

Material:Aluminum

Color:White/Gray

Optional:Triac PWM dim, 0-10V dim, DALI dim driver

3000K





Simulation effect



The material, pure aluminum Of high quality, lightness and grace, effectively heat dissipation, ensuring LED chip longer life span.

Ø68mm

Model: NL6FHF21

Power:6W

Input voltage:AC 220-240V

Beam angle:38°

Luminous Flux:550-650lm

CRI:Ra>80


CCT:3000K/4000K/5000K

Material:Aluminum

Color:White/Gray

Optional:Triac PWM dim, 0-10V dim, DALI dim driver





Model: NL8FHF21

Power:8W

Input voltage:AC 220-240V Beam angle:38°

Luminous Flux:750-850lm

CRI:Ra>80

CCT:3000K/4000K/5000K


Material:Aluminum

Color:White/Gray

Optional:Triac PWM dim, 0-10V dim, DALI dim driver

3000K





Simulation effect



Simulation effect



All types of public places, restaurants, shops, car showrooms, brand stores, department stores, supermarkets, museums, office halls, homes, etc.



Model: NLFHM31

Power:10W

Input voltage:AC 220-240V

Beam angle:100°

Luminous Flux:800-900lm

CRI:Ra>90

CCT:3000K/4000K/5000K


Material:Aluminum Color:White/Gray





Optional:Triac PWM dim, 0-10V dim,DALI dim driver



















Adopt space:

All types of public places, restaurants, shops, car showrooms, brand stores, department stores, supermarkets, museums, office halls, homes, etc.





NELUX HK INTERNATIONAL,LTD aporta al mundo del diseño de iluminación nuevos productos e ideas que puedan dar a los arquitectos, decoradores, interioristas, lighting designers, etc un amplio abanico de posibilidades para sus proyectos.

Nelux producing your dreams

NELUX HK INTERNATIONAL, LTD brings new products and ideas to the world of lighting design giving to architects, decorators, interior designers, lighting designers, etc. a wide range of possibilities to your projects projects.

Nelux producing your dreams

email

sales@nelux.com.hk salesnelux@gmail.com

skype

neluxlighting

wechat

neluxury

instagram

https://www.instagram.com/nelux_hk/